

Amendments to the Specification

Please replace the paragraph beginning line 16, page 2, with the following amended paragraph:

--FIG. 3 is a perspective view of a second preferred embodiment of the present invention with the crown plate being removed;--

Please replace the paragraph beginning line 18, page 2, with the following amended paragraph:

--FIG. 4 is a perspective view of a third preferred embodiment of the present invention with the crown plate being removed, and--

Please replace the paragraph beginning line 2, page 3, with the following amended paragraph:

--The housing 10 has a front portion on which a face 11 is mounted. The housing 10 further has a sole portion 12, a rear portion 13, a crown portion 14, a toe portion 15, a heel portion and a neck portion 16. The housing 10 has a chamber 17 inside. In this preferred embodiment, the housing 10 has an opening 18 at the crown portion 14. A crown plate 19 is provided to cover the opening 18. The housing has two bonding portions 101 and 102. The bonding portion 101 is disposed at a periphery of the opening 18 ~~and is adjacent to~~ on an upper portion 141 of the crown portion 14 adjacent to

Appln. No. 10/791,701
Amdt. dated June 22, 2005
Reply to Office Action of February 22, 2005

the front portion on which the face 11 is mounted. The
bonding portion 102 is disposed at the sole portion 12 and is
adjacent to the rear portion 13.--